



# SELF-TRACKING DOLLY COMBINATION FOR LONG LOADS

SPECIAL APPLICATIONS

---



**YOUR BENEFITS**

- ✓ High ground clearance below the load
- » Easy negotiation of obstacles on the route
  
- ✓ Low overall weight and less fuel consumption
- » Reduced overall transport costs
  
- ✓ Transports of different loads with >70 t payload possible
- » Flexible, future-proof transport solution
  
- ✓ Turntable steering angle +/- 100°
- » High agility, especially when maneuvering

**SELF-TRACKING DOLLY COMBINATION FOR LONG LOADS**  
 LIGHTWEIGHT, FLEXIBLE AND ECONOMICAL



**LOW OVERALL WEIGHT**



**HIGH AGILITY**



**MULTIPLE COMBINATIONS POSSIBLE**



**TECHNICAL DATA**

	<b>SX-U 2</b>	<b>SN-L 4 <sup>[1]</sup></b>
Axle load <i>(depending on country-related regulations)</i> <i>(technical)</i>	10-12 t at 80 km/h 12 t at 80 km/h	10-12 t at 80 km/h 12 t at 80 km/h
Axle stroke	200 mm (+/- 100 mm)	190 mm (+105 / - 85 mm)
Tires	twin tires 245/70 R 17.5 <sup>[2]</sup>	twin tires 245/70 R 17.5 <sup>[3]</sup>
Dead weight <sup>[4]</sup>	4.0 t	8.0 t
Vehicle width	2,550 mm	2,550 mm
Maximum steering angle		±50° steered axle ±20° training axle

<sup>[1]</sup> combination with SN-L 5 or various THP modules equally applicable

<sup>[2]</sup> optionally 315/80 R 22.5 tires possible

<sup>[3]</sup> optionally 285/70 R 19.5 tires possible

<sup>[4]</sup> depending on chosen tires

## SELF-TRACKING DOLLY COMBINATION FOR LONG LOADS TECHNICAL DATA



### TECHNICAL DATA

	SX-U 2	SN-L 4 <sup>[1]</sup>
Axle load <i>(depending on country-related regulations) (technical)</i>	10-12 t at 80 km/h 12 t at 80 km/h	10-12 t at 80 km/h 12 t at 80 km/h
Axle stroke	200 mm (+/- 100 mm)	190 mm (+105 / - 85 mm)
Tires	twin tires 245/70 R 17.5 <sup>[2]</sup>	twin tires 245/70 R 17,5 <sup>[3]</sup>
Dead weight <sup>[4]</sup>	4.0 t	8.0 t
Vehicle width	2,550 mm	2,550 mm
Maximum steering angle		±50° steered axle ±20° trainling axle



### ACCESSORIES

- + Inclined sprouts (easy foldable)
- + SX-U available with ball bearing race ring or fifth wheel coupling
- »SmartControl« (radio remote control for easy operation of all hydraulic functions)
- + Support trestle for height equality between front dolly and rear dolly
- + Adjustable pocket stakes at the turntable

<sup>[1]</sup> combination with SN-L 5 or various THP modules equally applicable

<sup>[2]</sup> optionally 315/80 R 22.5 tires possible

<sup>[3]</sup> optionally 285/70 R 19.5 tires possible

<sup>[4]</sup> depending on chosen tires



### GOLDHOFER AKTIENGESELLSCHAFT

Donaustrasse 95, 87700 Memmingen/Germany  
Telephone: +49 8331 15-0, Fax: +49 8331 15-239  
Web: www.goldhofer.com, E-Mail: info@goldhofer.com

### SALES

Telephone Sales Europe: +49 8331 15-341  
Telephone Sales International: +49 8331 15-342  
E-Mail: sales-transporttechnology@goldhofer.com

### SERVICES AND SPARE PARTS

Telephone: +49 8331 15-400, Fax: +49 8331 15-247  
Emergency Hotline: +49 172 837 61 65  
E-Mail: service-transporttechnology@goldhofer.com

**MADE FOR YOUR MISSION**