

Goldhofer TU-L 4

Trailer
FR 12/2018
Used vehicle

Price on request

More technical data

Vehicle Number	GT4784
Permissible Gross Vehicle Weight (GVW)	44.800 kg
HU	New
Axles	4
Load Capacity	35.700 kg
Vehicle Length	18.720 mm
Vehicle Width	2.550 mm
Loading Space Length	7.500 mm
Loading Space Width	2.550 mm

Features

ABS
EBS
Rental possible

Vehicle Description

GOLDHOFER 4-axle low-loader trailer type TU- L 4 "expert 4875"

-Weights:

- Axle load: 4 x 10,000 kg
- Total weight: 40,000 kg
- Dead weight: approx. 9,100 kg (without accessories)
- Payload: approx. 35,700 kg
- Dimension b - coupling length 11,670 mm

- Loading area:

- Loading area continuous over chassis with spruce floor covering
- Underride guard
- BPW-Eco axle make with mechanical axle compensation
- Excavator trough 2940 mm x 580 mm
- EC brake system, spring-loaded parking brake, EBS electronic braking system
- 1 pc. Spare wheel holder mounted under loading area
- Beveled" design (800 mm long, 10° bevel) with superGrip rubber coating in the chamfer
- Hydraulic support in the rear of the vehicle



- Rear: SuperGrip rubber
- Climbing rails on the outside of the chamfer 20 mm x 20 x 55 mm
- Ramps:
 - 1-piece hydraulic ramps (2850 mm x 720 mm) with Super-Grip rubber coating and Climbing ledges on the outside of the ramps (20 x 20 x 100 mm wide)
 - Max. Ramp load capacity 50,000 kg
 - Hydraulic ramp lifting gear
 - Mechanical ramp displacement; max. external width 2,780 mm, minimum internal distance 472 mm
 - Holder for rotating beacon incl. rotating beacon
- Load securing:
 - 6 pairs of lashing points LC 10000 daN
 - 3 pairs of lashing points LC 13400 daN
 - 1 pair of lashing points LC 20000 daN
 - 4 pairs of stanchion pockets (100 x 50 mm)
 - 4 pairs of stanchion pockets (100 x 50 mm) front center for load stop
 - 4 pairs of threaded bush(es) M36 on the loading surface
 - 1 pair of holes for attaching load blocks, type VLBG 2.5 (LC 5000)
 - 4 pairs of holes for attaching load blocks, type VLBG 1 (LC 2000)
- Accessories:
 - Lockable ALU cover for storage space on the offset
 - Drawbar 200 mm cranked, 1500 mm long with drawbar eye 50 mm diameter, with BPW-drawbar support
 - Tool box (plastic), mounted under the cargo bed
 - Foldable widening by 225 mm each and widening planks made of larch, 45 mm; incl. Brackets for widening planks under the cargo bed
 - 1 spare wheel, complete - 2 pairs of warning signs 423 mm x 423 mm (incl. LED position light)
 - Hydraulics: tractor connection and manual emergency pump
 - 1 pair of LED reversing lights on the end cross member
 - Plug-in rotating beacon
- SUBJECT TO PRIOR SALE -
- INFORMATION WITHOUT GUARANTEE -





GOLDHOFER AKTIENGESELLSCHAFT
Donaustrasse 95
87700 Memmingen/Germany

Tel.: +49 8331 15-0
Fax: +49 8331 15-239
Web: www.goldhofer.com

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15817
Fax: +49 8331 15817
eMail: philipp.grosse@goldhofer.com