

Goldhofer STZ-VL 3

Flat-bed trailer
FR 07/2008
Used vehicle

Price on request

More technical data

Vehicle Number GT 4762
HU New

Vehicle Description

GOLDHOFER 3-axle low-bed semi-trailer STZ-VL 3-33/80 A

Fifth wheel load: 18,000 kg
3 x 10t axle load: 30,000 kg
Total weight: 48,000 kg
Tare weight: approx. 15,500 kg (without accessories)
Payload: approx. 32,500 kg

- Gooseneck, hydraulic, with center beam
- Hydraulic lifting and lowering function incl. 2 support cylinders
- Forward deflection radius: 1,385 mm / rearward deflection radius: 2,800 mm
- King pin: 3.5"
- Hydraulic connection for tractor unit
- Special low bed in the form of an excavator bridge, welded directly to the 3-axle chassis
- Additional frame reinforcement for accessibility by tracked vehicles
- Length: 8,000 mm telescopic by 5,600 mm to 13,600 mm
- Basic width: 2,550 mm
- Overall height of the drop deck bridge: 320 mm
- 3-axle running gear (air-sprung):
- Axle make: BPW Eco
- Axle compensation, stroke 200 mm
- All three axles hydraulically forced steered
- Chassis width: 2,550 mm
- Wheelbase 2 x 1,310 mm
- Continuous excavator trough in the chassis; width 780 mm / length 4,100 mm
- Twin tires 235/75R17.5 143/141J
- easyControl "Comfort" steering system for manual steering of





GOLDHOFER AKTIENGESELLSCHAFT
Donaustrasse 95
87700 Memmingen/Germany

Tel.: +49 8331 15-0
Fax: +49 8331 15-239
Web: www.goldhofer.com

the trailer axles via radio remote control and cable remote control

- SUBJECT TO PRIOR SALE -
- INFORMATION WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com