

Goldhofer STN-L 3 (245) A »STEPSTAR«

Semi-trailers
FR 03/2023
Used vehicle

Price on request

More technical data

Vehicle Number GT4730

Vehicle Description

GOLDHOFER 3-axle low-loader semitrailer
Type STN-L 3 (245) A "STEPSTAR"

Fifth wheel load: 18,500 kg
3 x 10t axle load: 30,000 kg (technical max. 12t axle load)
Total weight: 48,500 kg
Tare weight: approx. 11,400 kg (without accessories)
Payload: approx. 37,100 kg
Dimension b: 11,870 mm

- Gooseneck
- Length: 3,700 mm
- Saddle height (loaded at loading height 1): 1,250 mm
- Heel height: 620 mm
- Rear steering radius: 2,300 mm
- Kingpin: 2"
- 3 x rectangular aluminum storage box with hinged lid, lockable
Dimensions (H x W x D) approx. 400 mm x 800 mm x 380 mm
(arrangement: left, right, center)
- Aluminum side panels 400 mm high
- Spare wheel holder at the front of the gooseneck

- Loading area:
- Length: 9,300 mm
- Width: 2,550 mm
- Technical maximum extension of 6,840 mm
(Please note: the maximum permissible overall length depends
on the country and tractor unit and therefore deviates from the
technical maximum length)
- Angled vehicle rear 8°, 550 mm length
- Mechanical, spring-supported comfort drop supports at the rear
of the vehicle for support during the loading process
- Traffideckgo® rubber flooring, construction height 8 mm
on the outside of the loading area (incl. rear slope, without fixed

part), with sanding

- 3 pairs of stanchion pocket strips
- 4 pairs of wader pockets for container transport (2 x 20" or 1 x 40")
- Open steel storage box for widening planks under the loading area

- 3-axle chassis:
 - Axle make: BPW Eco Max
 - 2 x rigid axle | 1 x friction steered axle
 - Loading height 1 (loaded): 855 mm +140 mm / -60 mm
 - Loading height 2 (loaded): 895 mm +/- 100 mm

- Ramp, 2-part
 - Length 4,300 mm, width 800 mm
 - Load capacity 38 t
 - Larch floor covering
 - Integrated mechanical lock in the ramp lifting cylinder to secure the ramp in transport position
 - Hydraulic ramp operation (lifting gear and shifting)
 - Spiral cable remote control with plug connection in the rear area
 - Electro-hydraulic unit for ramp operation

- SUBJECT TO PRIOR SALE -
- INFORMATION WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com