

Goldhofer STN L 3

Semi-trailers
FR 03/2020
Used vehicle

Price on request

More technical data

Vehicle Number	GT4592
Permissible Gross Vehicle Weight (GVW)	44.500 kg
HU	New
Axles	3
Load Capacity	34.700 kg

Features

ABS
EBS
Rental possible

Vehicle Description

GOLDHOFER 3-axle low-loader semitrailer
Type STN-L 3 (245)

fifth-wheel load: 14,500 kg
Axle load 3 x 10t: 30,000 kg
Total weight: 44,500 kg
Tare weight: approx. 9,800 kg (without accessories)
Payload: approx. 34,700 kg
Dimension b: 11,450 mm

- Gooseneck
- Length: 3,500 mm
- Saddle height (loaded at loading height 1): 1,230 mm
- Heel height: 875 mm
- Front / rear steering radius: 1,610 mm / 2,100 mm
- Kingpin: 2"

- Loading area:
- Length: 8,800 mm
- Width: 2,550 mm
- inclined vehicle rear 7.6°, 550 mm length
- Mechanical, spring-supported comfort drop supports at the rear of the vehicle for support during loading process



- Floor covering: Larch front and rear, rubber supergrip in between
- 3-axle running gear:
 - Axle make: BPW Eco
 - 2 x rigid axle | 1 x friction-steered axle
 - Loading height 1 (loaded): 855 mm +140 mm / -60 mm
 - Twin tires 245/70 R17.5
- Ramp, 2-part
 - Length 2,850 mm + 1,540 mm, width 1,040 mm
 - Ramp payload: 22t
 - Floor covering: Grating
 - Integrated mechanical lock in the ramp lifting cylinder to secure the ramp in the transport position
 - Hydraulic ramp operation (lifting gear and shifting)
 - Hydraulic function via motorized carriage, operation at rear right
- Miscellaneous
 - Spare wheel holder, 2 pieces in basket design, under loading area
 - Smart Board, made by Wabco
 - Central lubrication system, make BEKAMAX, 1 pump, without ramp supply
 - Rotating beacon
- SUBJECT TO PRIOR SALE -
- INFORMATION WITHOUT GUARANTEE -



Translated with DeepL.com (free version)

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustrasse 95
87700 Memmingen
Deutschland

philipp.grosse@goldhofer.com
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com