

Goldhofer STN-L 3 (245) A "STEPSTAR"

Semi-trailers
FR 08/2021
Used vehicle

Price on request

More technical data

Vehicle Number	GT4674
Permissible Gross Vehicle Weight (GVW)	48.500 kg
HU	New
Axles	3
Load Capacity	39.500 kg

Features

ABS
EBS
Rental possible

Vehicle Description

GOLDHOFER 3-axle low-loader semitrailer
Type STN-L 3 (245) A "STEPSTAR"

Fifth wheel load: 18,500 kg
3 x 10t axle load: 30,000 kg (technical max. 12t axle load)
Total weight: 48,500 kg
Tare weight: approx. 10,400 kg
Payload: approx. 38,100 kg
Dimension b: 12,000 mm

- Gooseneck
- Length: 4,100 mm
- Saddle height (loaded at loading height 1): 1,200 mm
- Rear steering radius: 2,400 mm
- Kingpin: 2"
- 3 x rectangular aluminum storage box with hinged lid, lockable
Dimensions (H x W x D) approx. 400 mm x 800 mm x 380 mm
(arrangement: left, right, center)
- Aluminum side panels 2 pieces 400 mm high
- Spare wheel holder at the front of the gooseneck
- Second screw-in position for the kingpin for subsequent
modification of the steering radius
rear steering radius between 2,400 mm and 2,100 mm (installed
at position 2,400 mm)



- Loading area:
- Length: 9,300 mm
- Width: 2,550 mm
- Technical maximum extension of 3,000 mm
(Attention: the maximum permissible overall length depends on the country and tractor unit and therefore deviates therefore differs from the technical maximum length)
- Angled vehicle rear 8°, 550 mm length
- Mechanical, spring-supported comfort drop supports at the rear of the vehicle for support when loading
loading process
- Steel with anti-slip
- 3 pairs of stanchion pocket rails
- 2 pairs of wader pockets for container transport (2 x 20")
- Crossbars for widening to 3,000 mm
- Excavator trough length (L5) x width (W2) x depth 3,850 mm x 760 mm x 310 mm
- 1x stanchion pocket rails on the fixed part
- 1x stanchion pocket rails approx. in the middle of the loading area
- 1x stanchion pocket rails behind the last axle

- 3-axle running gear:
- Axle make: BPW Eco Max
- 2 x rigid axle | 1 x friction-steered axle
- Loading height 1 (loaded): 855 mm +140 mm / -60 mm
- Loading height 2 (loaded): 895 mm +/- 100 mm
- Load-dependent lift axle on the first axle incl. start-up aid (forced lowering of the lift axle possible via TIM)

- Ramp, 2-part
- Length 4,300 mm, width 800 mm
- Load capacity 38 t
- Supergrip rubber floor covering
- Integrated mechanical lock in the ramp lifting cylinder to secure the ramp in the transport position
transport position
- Hydraulic ramp operation (lifting gear and shifting)
- Spiral cable remote control with plug connection in the rear area
- Electro-hydraulic unit for ramp operation
- Ramp mounted on the vehicle

- Accessories
- 1 pair of additional LED reversing lights rear switched to reverse gear

- 1 x plug-in LED rotating beacon, switched to lighting

- SUBJECT TO PRIOR SALE -
- INFORMATION WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland

philipp.grosse@goldhofer.com
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com