

Goldhofer STZ-VHL 6-60/80 A (2+4)

Flat-bed trailer
FR 12/2005
Used vehicle

Price on request

More technical data

Vehicle Number	GT4666
Construction Year	2005
Permissible Gross Vehicle Weight (GVW)	88.000 kg
HU-Date	12/2021
Axes	6
Load Capacity	60.000 kg
Vehicle Length	20.045 mm
Vehicle Width	2.750 mm
Loading Space Length	7.265 mm
Loading Space Width	2.750 mm

Features

Air suspension
ABS
Rental possible

Vehicle Description

GOLDHOFER 6-axle semi-trailer type STZ-VHL 6-60/80 A (2+4) consisting of STZ-VL 4 and THP/ET 2

Fifth-wheel load: 30,000 kg
2 x 12 to axle load: 24,000 kg
4 x 10 to axle load: 40,000 kg
Total weight: 94,000 kg
Tare weight (without accessories): approx. 28,000 kg
Payload: approx. 66,000 kg

- Gooseneck
- Saddle height loaded: 1,350 mm
- Rear steering radius: 2,800 mm
- Kingpin: 3.5"
- incl. motorized trailer hydraulic connection

- 2-axle THP/ET chassis
- Two single-wheel pendulum axle units with hydraulic axle compensation



- Width: 2,500 mm
- Axle compensation +/- 300 mm
- Axle make: BPW/Eco
- Tires: 285/70 R 19.5
- Both axles hydraulically forced-steered and counter-steered to the rear chassis

- Loading bridge
- Basic length in 0+4 combination: 7,650 mm
- Basic length in 2+4 combination: 7,365 mm
- Overall height: 300 mm
- Width: 2,750 mm
- Loading height:

Driving position 1: 380 mm, ground clearance: 80 mm

Driving position 2: 470 mm, ground clearance: 170 mm

- Easily telescopes by 5,100 mm
- Can be extended in steps of 500 mm, additional first locking step 250 mm
- Separation point for separating the rear chassis

- 4-axle STZ-V chassis
 - Air-sprung 4-axle running gear
 - Axle make BPW
 - all axles hydraulically forced steered
 - Two pre-adjusted ride heights and lifting/lowering valve for manual lowering or raising
 - Width: 2,750 mm
 - Axle stroke:
- Travel position 1: +205/-65 mm
Travel position 2: +115/-155 mm
- incl. excavator trough in the chassis

- Accessories:
- GOLDHOFER easyCONTROL "Comfort" steering system for manual steering by radio remote control
- Central lubrication system make "BEKA-MAX"

- SUBJECT TO PRIOR SALE -
- INFORMATION WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustrasse 95
87700 Memmingen
Deutschland
Tel.: +49833115817





GOLDHOFER AKTIENGESELLSCHAFT
Donaustrasse 95
87700 Memmingen/Germany

Tel.: +49 8331 15-0
Fax: +49 8331 15-239
Web: www.goldhofer.com

Fax: +4981570817
eMail: Philipp.Grosse@goldhofer.com