

Goldhofer STN-L 3 (245) "STEPSTAR"

Semi-trailers
FR 01/2022
New vehicle

Price on request

More technical data

Vehicle Number N104144800
Construction Year 2022

Features

Air suspension
ABS
EBS
Rental possible

Vehicle Description

GOLDHOFER 3-axle low-loader semitrailer
Type STN-L 3 (245) "Stepstar"

Fifth wheel load: 18,500 kg
3 x 10t axle load: 30,000 kg (technical max. 12t axle load)
Total weight: 48,500 kg
Tare weight: approx. 9,000 kg (with accessories)
Payload: approx. 39,500 kg
Dimension b: 11,370 mm

- Gooseneck
- Length: 4,100 mm
- Saddle height: 1,270 mm
- Forward deflection radius: 1,690 mm
- Rear deflection radius: 2,400 mm
- Kingpin: 2"
- Anti-slip coating
- Spare wheel holder on the front of the gooseneck
- 3 pairs of lashing rings on loading area gooseneck
- 2 pairs of stake pockets

- Loading area
- Length: 8,700 mm
- Width: 2,550 mm
- Not extendable
- Sloping vehicle rear 8°, 550 mm long
- Traffideckgo® rubber floor covering, sanded, construction height

- 8 mm (shortened version, in front of the axles)
- Sheet metal floor covering with anti-slip coating
 - Open steel storage box for widening planks mounted under the loading area, width 800 mm
(max. payload 200 kg with flat load)
 - Mechanical spring-supported rear support
 - 7 pairs of stanchion pockets in the outer frame of the cargo bed
 - 9 lashing points on cargo bed/rear area/outer frame (LC 10,000)
 - Open steel storage box for widening planks under the cargo bed
 - Extendable widening 3 m
-
- 3-axle running gear:
 - Axle make: BPW Eco Max
 - 2 x rigid axle | 1 x friction steered axle
 - Loading height 1 (loaded): 855 mm +140 mm / -60 mm
 - Loading height 2 (loaded): 895 mm +/- 100 mm
 - Driving stability control RSS (Roll Stability Support)
 - Excavator trough: L 3,050 mm x W 760 mm x H 310 mm
-
- Ramp, 1-piece
 - Length 3,000 mm, width 800 mm
 - Load capacity 38 t
 - Larch floor covering
 - Integrated mechanical lock in the ramp lifting cylinder to secure the ramp in the transport position
 - transport position
 - Hydraulic ramp operation (lifting gear and shifting)
 - Spiral cable remote control with plug connection in the rear area
 - Electro-hydraulic unit for ramp operation
-
- Systems
 - High-quality ERMAX vehicle electrics

DB 7350 - nova gray

- SUBJECT TO PRIOR SALE -
- INFORMATION WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: 0833115817
eMail: philipp.grosse@goldhofer.com