

Goldhofer STN-L 3 (245) A "STEPSTER"

Semi-trailers
FR 04/2024
New vehicle

Price on request

More technical data

Vehicle Number 43234
Construction Year 2024

Features

Air suspension
ABS
EBS
Rental possible

Vehicle Description

GOLDHOFER 3-axle flatbed semi-trailer
Type STN-L 3 (245) A "Stepstar"

Maximum permissible laden weight: 18,500 kg
3 x 10 t Axle load: 30,000 kg (technical max. 12t axle load)
Gross vehicle weight: 48,500 kg
Dead weight: approx. 11,000 kg (without accessories)
Payload: approx. 37,500 kg
Dimension b: 11,370 mm

- >MEGA> gooseneck - low overall height, rigid in center tube design
 - Length: 3,700 mm
 - Fifth wheel height: 950 mm
 - Forward deflection radius: 1,845 mm
 - Backward deflection radius: 2,100 mm
 - King pin: 2"
 - Anti-slip covering
 - Spare wheel holder on the front of the gooseneck
 - 3 pairs of lashing rings on the loading area of the gooseneck
 - 2 pairs of stanchion pockets
- Loading area
 - Length: 9,300 mm (total length: 16,140 mm)
 - Width: 2,550 mm
 - Extendable: 6840 mm
 - Loading height : 855 mm (-60 mm / +140 mm)



- Beveled rear of vehicle 8°, 550 mm in length
- Sheet metal floor covering with anti-slip covering
- Open steel storage box for extension planks mounted under the loading area, width 800 mm
(max. payload 200 kg with even load distribution)
- Rear support mechanically spring-loaded
- 7 pairs of stanchion pockets in the outer frame of the loading area
- 9 lashing points on loading area/rear area/outer frame (LC 10,000)
- open steel storage box for extension planks under the loading area
- extendable extension 3 m

- 3-axle chassis:
 - wheelbase: 2 x 1,410 mm
 - Axle make: BPW Eco Max, air-suspended
 - 2 x rigid axle | 1 x friction-steered axle
 - Second loading height : 895 mm (-100 mm / +100 mm)
 - RSS (Roll Stability Support)
 - Excavator recess: L 3,050 mm x W 760 mm x H 310 mm

- 2-part ramp
 - Length 4,300 mm, width 800 mm
 - Load capacity 38 t
 - Larch floor covering
 - Integrated mechanical locking mechanism in the ramp lifting cylinder
for securing the ramp in the transport position
 - Hydraulic ramp operation (lifting and shifting)
 - Spiral cable remote control with plug connection at the rear
 - Electro-hydraulic unit for ramp operation

- Systems
 - High-quality ERMAX vehicle electrics

- RAL 3002 - Carmine red

- !!! SAMPLE IMAGES !!! -
- SUBJECT TO THE INTERMEDIATE SALE -
- INFORMATION WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95



GOLDHOFER AKTIENGESELLSCHAFT
Donaustrasse 95
87700 Memmingen/Germany

Tel.: +49 8331 15-0
Fax: +49 8331 15-239
Web: www.goldhofer.com

87700 Memmingen
Deutschland
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com