

Goldhofer STN-L 3 (245) RM2 "STEPSTAR"

Semi-trailers
FR 03/2022
Used vehicle

Price on request

More technical data

Vehicle Number GT0131
Construction Year 2021

Vehicle Description

GOLDHOFER 3-axle semi-trailer low loader
STN-L 3 (245) A RM2 "STEPS"

Saddle load: 18,500 kg
Axle load 3 x 10 t: 30,000 kg
Total weight: 48,500 kg
Tare weight: approx. 9,900 kg (without accessories)
Payload: approx. 38,600 kg
Dimension b: 11,370 mm

- Gooseneck
 - Length: 3,700 mm
 - Fifth wheel height (loaded at loading height 1): 1,270 mm
 - Step height: 855 mm
 - Steering radius to front/rear: 1,640 mm / 2,400 mm
 - Kingpin: 2"
- Loading area:
 - Length: 8,700 mm
 - Width: 2,550 mm
 - Sloped vehicle rear 8°, 550 mm length
 - Mechanical, spring-assisted comfort drop supports at the rear of the vehicle
 - Floor covering: Steel with anti-slip
- 3-axle chassis:
 - Width 2,550 mm
 - Excavator trough: Length 3,450 mm Width 760 mm Depth 310 mm
 - Axle manufacturer: BPW Eco
 - 2 x rigid axle | 1 x friction-steered axle



- Loading height 1 (loaded): 855 mm +140 mm / -60 mm
- Twin tires 245/70 R17.5
- Ramp, 1-piece
 - Length 3,000 mm, width 800 mm
 - Ramp payload: 38t
 - Floor covering: super grip
 - Integrated mechanical lock in ramp lifting cylinder, ramp safety device
 - Ramp operation (lifting and movement) hydraulic
- Miscellaneous
 - Wheel well cover/aluminum "Premium," full width 600 mm and extendable to 3,000 mm with 8 t wheel load; different wheel recess depths through use of wheel recess cover (depth approx.: 390 mm and 260 mm)
 - Smart Board, made by Wabco
 - TIM Knorr, ramp supply via electric unit (NATO socket)
 - High-quality ERMAX vehicle electrics
 - Rotating beacon
 - Single-color paint finish in DB7350 - Novagrau
- SUBJECT TO PRIOR SALE -
- INFORMATION PROVIDED WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com