

Goldhofer STN-L 4 (245) A RM2 "STEPSTAR"

Semi-trailers
FR 04/2025
Used vehicle

Price on request

More technical data

Vehicle Number GT2100451
Construction Year 2024

Features

Rental possible

Vehicle Description

GOLDHOFER 4-axle low-loader semi-trailer
STN-L 4 (245) A RM2 "STEPSTAR"

Semi-trailer load: 18,500 kg
Axle load 4 x 10 t
Total weight: 58,500 kg
Unladen weight: approx. 11,900 kg (without accessories)
Payload: approx. 46,600 kg
Dimension b: 11,870 mm

- Gooseneck
 - Length: 3,700 mm
 - Fifth wheel height (loaded at loading height 1): 1,300 mm
 - Steering radius to the front/rear: 1,705 mm / 2,300 mm
 - Kingpin: 2"
- Loading area:
 - Length: 9,300 mm
 - Simple extension 3,740 mm
 - Width: 2,550 mm
 - Loading height 1 (loaded): 855 mm +140 mm / -60 mm
 - Floor covering: Steel with anti-slip
- 4-axle chassis:
 - Width 2,550 mm
 - Excavator trough: Length 3,450 mm Width 760 mm Depth 310 mm
 - Sloped vehicle rear 8°, 550 mm length



- Mechanical, spring-assisted comfort drop supports at the rear of the vehicle
- Axle manufacturer: BPW Eco Max
- 2 x rigid axles | 2 x friction-steered axles
- Twin tires 245/70 R17.5

- Ramp, 2-piece
 - Length 2,750 mm + 1,550 mm, width 800 mm
 - Ramp payload: 38 t
 - Floor covering: larch
 - Ramp operation (lifting and shifting) hydraulic

- Miscellaneous
 - Wheel recess cover/aluminum "Premium," full width 600 mm and extendable to 3,000 mm with 8 t wheel load; different wheel recess depths through use of wheel recess cover (depth approx.: 390 mm and 260 mm)
 - Smart Board, make Wabco
 - TIM Knorr, power supply ramps via electric unit (NATO socket)
 - High-quality ERMAX vehicle electrics
 - Rotating beacon
 - Single-color paint finish in RAL 3003 ruby red

- SUBJECT TO PRIOR SALE -
- INFORMATION PROVIDED WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com