

Goldhofer STZ-VP/MPA 4 (245) A (1+3) mit Flachbettbrücke

Flat-bed trailer
FR 01/2018
Used vehicle

Price on request

More technical data

Vehicle Number	GT0179
Construction Year	2018

Vehicle Description

GOLDHOFER 4-axle flatbed, extendable
STZ-VP/MPA 4 (245) A (1+3) with flatbed bridge

Technical data when using a 3-axle tractor unit

Speed 80 km/h
Saddle load 17,000 kg
Axle load 4 x 12,000 kg
Permissible total weight approx. 65,000 kg
Unladen weight approx. 21,000 kg
Payload approx. 44,000 kg

Technical data when using a 4-axle tractor unit

Speed 80 km/h
Saddle load 20,500 kg
Axle load 4 x 12,000 kg
Permissible total weight approx. 68,500 kg
Unladen weight approx. 21,000 kg
Payload approx. 47,500 kg

Type STZ-VP 1 (245)

- Vehicle dimensions:
 - Dimension a: 5,350 mm
 - Dimension b: 16,050 mm
 - Total train length: 21,400 mm
- Gooseneck in center beam design:
 - Length. 3,700 mm
 - Width 2,480 mm
 - Saddle height (loaded): 1,300 mm



- Front steering radius: 1,280 mm
- Rear steering radius: 2,700 mm
- Kingpin: 2"
- Tractor unit fifth wheel height loaded: 1,296 mm
- Hydraulic lifting and lowering function with hydraulic differential switch

- Rear chassis:

- Axle manufacturer: BPW Eco Plus
- Axle lift (1): + 400 mm / - 200 mm
- All axles hydraulically steered
- Tires: 245/70R17.5 146/146F
- Excavator/bucket 3,960 mm long and approx. 860 mm wide
- easyCONTROL "Comfort" rear steering
- Central lubrication system, make "BEKA-MAX"
- Hydraulic axle compensation (stroke approx. 600 mm -200 mm / + 400 mm)

- Miscellaneous

- Aluminum side walls, 4-sided (with rear wall)
- Goldhofer "Premium" storage box
- Spare wheel holder, mounted upright on the loading area
- 2 spare wheels (1 x for front, 1 x for rear chassis)
- Reversing camera

MPA-V 3 (245) A

- Flatbed loading area:

- Length: 7,500 mm
- Width: 2,750 mm
- Height of low-bed bridge: 300 mm
- Beam width (outer tube): approx. 720 mm
- Easily telescopic by 1,500 mm to a maximum of 9,000 mm
- 1-piece mechanically folding ramp, length x width approx. 800 mm x 550 mm

- Chassis:

- Axle manufacturer: BPW Eco Plus
- All axles hydraulically forced steering
- Pendulum axles: stroke 350 mm

- Wheelbase: 1,510 mm
- Tires: 245/70R17.5
- Excavator trough: 4,580 mm long x 805 mm wide x 380 mm deep
- Central lubrication system, make: "BEKA-MAX"
- Follow-up steering
- Spray galvanized; paint finish: MB 7708 - silver gray
- SUBJECT TO PRIOR SALE -
- INFORMATION PROVIDED WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Philipp Grosse
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15-817
eMail: philipp.grosse@goldhofer.com